Commodity	Hot and cold rolled stainless steelcoil/sheet/strip
Grade (ASTM UNS)	304、304L、321、316、316L、317L、347H、309S、310S、904L、S32205、2507、254SMOS、32760、S31703、S31603、316Ti、S31635、S31254、N08926、2205、S32205、S31008、S30908、S32750、S32760、630etc
Grade (EN)	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4410, 1.4501, 1.4462, 1.4845, 1.4542, etc
Standard	ISO,JIS,ASTM,AS EN,GB
surface	NO.1, NO.2D, NO.2B, BA, NO.3, NO.4, NO.240, NO.320, NO.400, HL, NO.7, NO.8, etc
Length	2000mm, 2438mm, 3000mm, 5800mm, 6000mm, 12000mm, etc
Thickness	0.05-200mm(general); 0.01-0.05mm(stainless steel foil)
Width	10-2000mm
Coil weight	3-20MT/Coil or as your request
MOQ	5MT
Packaging	Export standard, seaworthy
ID	508mm or 610mm
Trade Term	FOB, CFR, CIF
Transport Type	Container,bulk and train
Payment terms	T/T, L/C at sight,West Union,D/P,D/A,Paypal

Product Name	Stainless steel pipe	
Technique:	Cold Rolled Hot Rolled	
Grade	304、304L、321、316、316L、317L、347H、309S、310S、904L、S32205、2507、254SMOS、32760、S31703、S31603、316Ti、 S31635、S31254、N08926、2205、S32205、S31008、S30908、S32750、S32760、630etc	
	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4410, 1.4501, 1.4462, 1.4845, 1.4542, etc	
Thickness:	0.3-150mm, (SCH10-XXS)	
Length	2000-12000mm	
Diameter	8-2500mm (3/8"-100")	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Application	High temperature components such as turbine blades, guide vanes, turbine disks, high pressurecompressor disks,machine manufacturingand combustion chambers used in the manufacture of aviation, naval and industrial gas turbines	
Packaging	cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands	
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft		
HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM		

Product Name	Stainless steel bar	
Technique:	Cold Rolled Hot Rolled	
Grade	304、304L、321、316、316L、317L、347H、309S、310S、904L、S32205、2507、254SMOS、32760、S31703、S31603、316Ti、S31635、S31254、N08926、2205、S32205、S31008、S30908、S32750、S32760、630etc	
	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4410, 1.4501, 1.4462, 1.4845, 1.4542, etc	
Length	2000-12000mm	
Diameter	4-500mm	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Application	High temperature components such as turbine blades, guide vanes, turbine disks, high pressurecompressor disks,machine manufacturingand combustion chambers used in the manufacture of aviation, naval and industrial gas turbines	
Packaging	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands	
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM		

Commodity	Hot and cold rolled stainless steelcoil/sheet/strip
Grade (ASTM UNS)	304、304L、321、316、316L、317L、347H、309S、310S、904L、S32205、2507、254SMOS、32760、S31703、S31603、316Ti、S31635、S31254、N08926、2205、S32205、S31008、S30908、S32750、S32760、630etc
Grade (EN)	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4410, 1.4501, 1.4462, 1.4845, 1.4542, etc
Standard	ISO,JIS,ASTM,AS EN,GB
surface	NO.1, NO.2D, NO.2B, BA, NO.3, NO.4, NO.240, NO.320, NO.400, HL, NO.7, NO.8, etc
Length	2000mm, 2438mm, 3000mm, 5800mm, 6000mm, 12000mm, etc
Thickness	0.05-200mm(general); 0.01-0.05mm(stainless steel foil)
Width	10-2000mm
Coil weight	3-20MT/Coil or as your request
MOQ	5MT
Packaging	Export standard, seaworthy
ID	508mm or 610mm
Trade Term	FOB, CFR, CIF
Transport Type	Container,bulk and train
Payment terms	T/T, L/C at sight,West Union,D/P,D/A,Paypal

Product Name	Stainless steel flange	
	410, 430, 201, 304, 304L, 321, 316, 316L, 317L, 347H, 309S, 310S, 904L, S32205, 2507, 254SMOS, 32760,	
Grade	253MA, N08926, etc.	
Graue	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4562, 1.4410, 1.4878, 1.4845,	
	1.4828, 1.4876, 2.4858, 2.4819	
Thickness	0.3-150mm, (SCH10-XXS)	
Specifications	10-1220mm, (3/8"-100") etc.	
Pressure	PN0.5-PN500	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Parlianian.	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer	
Packaging	requirements or products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands	
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft		
HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM		

Product Name:	Stainless steel Angle	
	410, 430, 201, 304, 304L, 321, 316, 316L, 317L, 347H, 309S, 310S, 904L, S32205, 2507, 254SMOS, 32760, 253MA,	
Grade	N08926, etc.	
Graue	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4562, 1.4410, 1.4878, 1.4845, 1.4828,	
	1.4876, 2.4858, 2.4819	
Thickness:	3-50mm	
Length:	6000mm 5800mm 12000mm or Customized	
Technique:	Cold Drawing or Hot Rolled or Casting	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Packaging	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or	
Fackaging	products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands	
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft		

HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM

Product Name	Stainless steel tee	
Grade	410, 430, 201, 304, 304L, 321, 316, 316L, 317L, 347H, 309S, 310S, 904L, S32205, 2507, 254SMOS, 32760, 253MA,	
	N08926, etc.	
	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4562, 1.4410, 1.4878, 1.4845, 1.4828,	
	1.4876, 2.4858, 2.4819	
Wall Thickness:	SCH10, SCH20, SCH30, STD, SCH40, SCH60, SCH80, SCH100 SCH120, SCH160, XS, XXS	
Size	1/2" -48" (Dn15-Dn1200)	
Surface:	nature color, varnished, black painting, anti-rust oil etc.	
Туре:	Equal/Straight tee,reduced tee,Y tee,lateral tee,Barred tee,split tee,tee cross	
MODEL:	1.Tee(Straight and Reducing) 2.180 DEG Return	
Connection	bevel end/BE/buttweld	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Packaging	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or	
	products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands		
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft		
HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM		

Product Name	Stainless steel elbow
Surface:	pickle sand, polished, Black paint, Antirust oli, Primary Color
Grade	410, 430, 201, 304, 304L, 321, 316, 316L, 317L, 347H, 309S, 310S, 904L, S32205, 2507, 254SMOS, 32760, 253MA, N08926, etc.
	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4562, 1.4410, 1.4878, 1.4845, 1.4828, 1.4876, 2.4858, 2.4819
Thickness	0.1-150mm / SCH5-SCH160-SCHXXS
R	1D, 1.5D etc, as required
Diameter	1-1500mm
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc
Inspection	ISO,SGS,BV and so on.
Туре:	seamless elbow, welded elbow
Degree:	45 degree, 90 degree, 180 degree
Packaging	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or products
Payment Terms	T/T L/C and Western Union etc
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM	

Product Name:	Stainless steel channel	
	410, 430, 201, 304, 304L, 321, 316, 316L, 317L, 347H, 309S, 310S, 904L, S32205, 2507, 254SMOS, 32760, 253MA,	
Grade	N08926, etc.	
Graue	1.4301, 1.4307, 1.4541, 1.4401, 1.4404, 1.4571, 1.4438, 1.4539, 1.4547, 1.4529, 1.4562, 1.4410, 1.4878, 1.4845, 1.4828,	
	1.4876, 2.4858, 2.4819	
Dimensions:	50 * 37 * 4.5-400 * 104 * 14.5 75 * 40 * 3.8 * 7-152 * 76 * 6.4 * 9140 * 60 * 7 * 10-200 * 75 * 8.5 * 11.5	
Length:	6m, 9m, 12m or as customerrequirement	
Standard	GB,AISI,ASTM,DIN,EN,SUS,UNS etc	
Inspection	ISO,SGS,BV and so on.	
Packaging	1. cases packed in wooden cases2. paper packaging3. plastic packing4. foam packagingPackaging according to customer requirements or	
1 dollaging	products	
Payment Terms	T/T L/C and Western Union etc	
Packaging & Delivery	in bundle,plastic bags,thin film,wooden pallet,standard seaworthy export packing or as customer demands	
20ft GP:5898mm(Length)x2352mm(Width)x2393mm(High) 24-26CBM40ft GP:12032mm(Length)x2352mm(Width)x2393mm(High) 54CBM40ft		
HC:12032mm(Length)x2352mm(Width)x2698mm(High) 68CBM		